

PGDQ2.MH14014

Marking and Labeling Systems - Component

No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
MIRMYR						
	Alkyd paint (AK PT)	150	-40	X	-	O
	Aluminum (AL)	150	-40	X	-	O
	Epoxy paint (EP PT)	150	-	X	-	-
	Galvanized steel (GS)	150	-40	X	-	O
	Melamine (ME)	100	-29	X	-	O
	Nylon - polyamide (PA)	100	-29	X	-	O
	Phenolic - Phenol Formaldehyde (PH)	100	-29	X	-	O
	Polycarbonate (PC)	100	-29	X	-	O
	Polyester paint (PER PT)	100	-29	X	-	O
	Polyester powder paint (PER PDR PT)	100	-40	X	-	-
	Porcelain (PRCLN)	100	-29	X	-	O
	Stainless steel (SS)	100	-29	X	-	O
	Acrylic paint (AC PT)	80	-40	X	-	O
	Acrylonitrile butadiene styrene (ABS)	80	-40	X	-	O
	Polypropylene (PP)	80	-	X	-	O
	Polystyrene (PS)	80	-29	X	-	O
	Unsaturated polyester - thermoset (UP)	80	-40	X	-	O