

PGDQ2.MH14014

Marking and Labeling Systems - Component

No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
MIRMYR D, MIRMYR 2D						
	Aluminum (AL)	150	-40	X	X	O, G
	Acrylic paint (AC PT)	125	-40	X	X	O, G
	Alkyd paint (AK PT)	125	-40	X	X	O, G
	Epoxy paint (EP PT)	125	-40	X	X	-
	Epoxy powder paint (EP PDR PT)	125	-40	X	-	O
	Epoxy/urethane powder paint	125	-40	X	X	-
	Galvanized steel (GS)	125	-40	X	X	-
	Polyester paint (PER PT)	125	-40	X	X	O, G
	Polyester powder paint (PER PDR PT)	125	-40	X	X	-
	Porcelain (PRCLN)	125	-40	X	X	-
	Stainless steel (SS)	125	-40	X	X	-
	Phenolic - Phenol Formaldehyde (PH)	100	-40	X	X	-
	Acrylonitrile butadiene styrene (ABS)	80	-40	X	X	O, G
	Melamine (ME)	80	-40	X	X	-
	Nylon - polyamide (PA)	80	-40	X	X	O, G
	Polybutylene terephthalate (PBT)	80	-40	X	X	O
	Polycarbonate (PC)	80	-40	X	X	-
	Polypropylene (PP)	80	-	X	-	O, G
	Unsaturated polyester - thermoset (UP)	80	-40	X	X	-
	Polystyrene (PS)	60	-40	X	X	O

PGDQ8.MH14014

Marking and Labeling Systems Certified for Canada - Component

Model No.	Application Surface	Max Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
MIRMYR D, MIRMYR 2D (Type A)					
	Metals	150	X	X	-
	Plastic Group I	100	X	X	-
	Plastic Group II	80	X	X	-
	Plastic Group III	80	X	X	-
	Plastic Group IV	80	X	X	-

	Plastic Group V	80	X	X	-
	Plastic Group VI	80	X	X	-
	Plastic Group VII	80	X	X	-
	Plastic Group VIII	80	X	X	-