

## PGDQ2.MH14014

### Marking and Labeling Systems - Component

No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
<b>MIRMYR V</b>						
	Acrylic paint (AC PT)	100	-40	X	X	-
	Alkyd paint (AK PT)	100	-40	X	X	-
	Aluminum (AL)	100	-40	X	X	-
	Epoxy paint (EP PT)	100	-40	X	X	-
	Epoxy powder paint (EP PDR PT)	100	-40	X	X	-
	Galvanized steel (GS)	100	-40	X	X	-
	Melamine (ME)	100	-40	X	X	-
	Nylon - polyamide (PA)	100	-40	X	X	-
	Phenolic - Phenol Formaldehyde (PH)	100	-	X	-	-
	Polycarbonate (PC)	100	-40	X	X	-
	Polyester paint (PER PT)	100	-40	X	X	-
	Polyester powder paint (PER PDR PT)	100	-40	X	X	-
	Polyurethane paint (PUR PT)	100	-40	X	X	-
	Porcelain (PRCLN)	100	-40	X	X	-
	Stainless steel (SS)	100	-40	X	X	-
	Unsaturated polyester - thermoset (UP)	100	-40	X	X	-
	Acrylonitrile butadiene styrene (ABS)	80	-40	X	X	-
	Polypropylene (PP)	80	-	X	-	-
	Polystyrene (PS)	80	-40	X	X	-

## PGDQ8.MH14014

### Marking and Labeling Systems Certified for Canada - Component

Model No.	Application Surface	Max Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
<b>MIRMYR V (Type A)</b>					
	Electrostatic coated metal A	100	X	X	-
	Electrostatic coated metal C	100	X	X	-
	Electrostatic coated metal D	100	X	X	-
	Metals	100	X	X	-

	Plastic Group I	100	X	X	-
	Plastic Group II	80	X	X	-
	Plastic Group III	80	X	X	-
	Plastic Group IV	80	X	X	-
	Plastic Group V	80	X	X	-
	Plastic Group VI	80	X	X	-
	Plastic Group VII	80	X	X	-
	Plastic Group VIII	80	X	X	-