

**PGDQ2.MH14014**  
**Marking and Labeling Systems - Component**

No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
<b>MIRVY</b>						
	Acrylic paint (AC PT)	80	-29	X	-	O
	Alkyd paint (AK PT)	80	-29	X	-	O
	Aluminum (AL)	80	-29	X	-	O
	Epoxy painted metal	80	-	X	-	O
	Galvanized steel (GS)	80	-40	X	-	O
	Porcelain (PRCLN)	80	-40	X	-	O
	Stainless steel (SS)	80	-29	X	-	O
	Unsaturated polyester - thermoset (UP)	80	-29	X	-	O
	Acrylonitrile butadiene styrene (ABS)	60	-29	X	-	O
	Polyphenylene oxide/ether (PPOX)	60	-	X	-	-
	Polystyrene (PS)	60	-	X	-	-
	Polypropylene (PP)	40	-29	X	-	-

**PGDQ8.MH14014**  
**Marking and Labeling Systems Certified for Canada -  
Component**

Model No.	Application Surface	Max Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
<b>MIRVY (Type A)</b>					
	Metals	100	X	-	-
	Plastic Group I	100	X	-	-
	Plastic Group II	80	X	-	-
	Plastic Group III	80	X	-	-
	Plastic Group V	80	X	-	-
	Plastic Group VI	80	X	-	-
	Plastic Group VII	80	X	-	-
	Plastic Group VIII	80	X	-	-