

PGDQ2.MH14014

Marking and Labeling Systems - Component

No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
MIRVY V						
	Acrylic paint (AC PT)	80	-40	X	X	-
	Acrylonitrile butadiene styrene (ABS)	80	-40	X	X	-
	Alkyd paint (AK PT)	80	-40	X	X	-
	Aluminum (AL)	80	-40	X	X	-
	Epoxy paint (EP PT)	80	-40	X	X	-
	Galvanized steel (GS)	80	-40	X	X	-
	Melamine (ME)	80	-40	X	X	-
	Nylon - polyamide (PA)	80	-40	X	X	-
	Phenolic - Phenol Formaldehyde (PH)	80	-40	X	X	-
	Polybutylene terephthalate (PBT)	80	-40	X	X	-
	Polycarbonate (PC)	80	-40	X	X	-
	Polyester paint (PER PT)	80	-40	X	X	-
	Polyester powder paint (PER PDR PT)	80	-40	X	X	-
	Polyethylene (PE)	80	-40	X	X	-
	Polyphenylene oxide/ether (PPOX)	80	-40	X	X	-
	Polypropylene (PP)	80	-40	X	X	-
	Polystyrene (PS)	80	-40	X	X	-
	Polyvinyl chloride (PVC)	80	-40	X	X	-
	Porcelain (PRCLN)	80	-40	X	X	-
	Stainless steel (SS)	80	-40	X	X	-
	Unsaturated polyester - thermoset (UP)	80	-40	X	X	-
	EPDM rubber	40	-	X	-	-

PGDQ8.MH14014

Marking and Labeling Systems Certified for Canada - Component

Model No.	Application Surface	Max Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
--------------	------------------------	---------------------	---------------	----------------	--------------------------

MIRVY V (Type A)					
	Metals	100	X	X	-