



# IMPROVED CERTIFICATIONS SEARCH TOOL. REGISTER NOW!

[LEARN MORE](#)

**PGDQ2.MH14014**

**Marking and Labeling Systems - Component**

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

**Marking and Labeling Systems - Component**

[See General Information for Marking and Labeling Systems - Component](#)

**MR LABEL INC**  
5018 Gray Rd  
Cincinnati, OH 45232-1514 USA

MH14014

Model No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
<b>Pressure-sensitive printed labels.</b>						
<b>MIRMYR</b>						
	Alkyd paint	150	-40	X	-	O
	Aluminum	150	-40	X	-	O
	Epoxy paint	150	-	X	-	-
	Galvanized steel	150	-40	X	-	O
	Melamine	100	-29	X	-	O
	Nylon - Polyamide	100	-29	X	-	O
	Phenolic - Phenol Formaldehyde	100	-29	X	-	O
	Polycarbonate	100	-29	X	-	O
	Polyester paint	100	-29	X	-	O
	Polyester powder paint	100	-40	X	-	-
	Porcelain	100	-29	X	-	O
	Stainless steel	100	-29	X	-	O
	Acrylic paint	80	-40	X	-	O
	Acrylonitrile butadiene styrene	80	-40	X	-	O
	Polypropylene	80	-	X	-	O
	Polystyrene	80	-29	X	-	O
	Unsaturated polyester - thermoset	80	-40	X	-	O
<b>MIRMYR D, MIRMYR 2D</b>						
	Aluminum	150	-40	X	X	O, G
	Acrylic paint	125	-40	X	X	O, G
	Alkyd paint	125	-40	X	X	O, G
	Epoxy paint	125	-40	X	X	-
	Epoxy powder paint	125	-40	X	-	O
	Epoxy/Urethane powder paint	125	-40	X	X	-
	Galvanized steel	125	-40	X	X	-
	Polyester paint	125	-40	X	X	O, G
	Polyester powder paint	125	-40	X	X	-
	Porcelain	125	-40	X	X	-
	Stainless steel	125	-40	X	X	-
	Phenolic - Phenol Formaldehyde	100	-40	X	X	-
	Acrylonitrile butadiene styrene	80	-40	X	X	O, G
	Melamine	80	-40	X	X	-
	Nylon - Polyamide	80	-40	X	X	O, G
	Polybutylene terephthalate	80	-40	X	X	O
	Polycarbonate	80	-40	X	X	-

	Polypropylene	80	-	X	-	O, G
	Unsaturated polyester - thermoset	80	-40	X	X	-
	Polystyrene	60	-40	X	X	O
<b>MIRMYR II</b>						
	Alkyd paint	150	-40	X	-	O
	Aluminum	150	-40	X	-	O
	Epoxy paint	150	-	X	-	-
	Galvanized steel	150	-40	X	-	O
	Melamine	100	-29	X	-	O
	Nylon - Polyamide	100	-29	X	-	O
	Phenolic - Phenol Formaldehyde	100	-29	X	-	O
	Polycarbonate	100	-29	X	-	O
	Polyester paint	100	-29	X	-	O
	Polyester powder paint	100	-40	X	-	-
	Porcelain	100	-29	X	-	O
	Stainless steel	100	-29	X	-	O
	Acrylic paint	80	-40	X	-	O
	Acrylonitrile butadiene styrene	80	-40	X	-	O
	Polypropylene	80	-	X	-	O
	Polystyrene	80	-29	X	-	O
	Unsaturated polyester - thermoset	60	-40	X	-	O
<b>MIRMYR V</b>						
	Acrylic paint	100	-40	X	X	-
	Alkyd paint	100	-40	X	X	-
	Aluminum	100	-40	X	X	-
	Epoxy paint	100	-40	X	X	-
	Epoxy powder paint	100	-40	X	X	-
	Galvanized steel	100	-40	X	X	-
	Melamine	100	-40	X	X	-
	Nylon - Polyamide	100	-40	X	X	-
	Phenolic - Phenol Formaldehyde	100	-40	X	-	-
	Polycarbonate	100	-40	X	X	-
	Polyester paint	100	-40	X	X	-
	Polyester powder paint	100	-40	X	X	-
	Polyurethane powder paint	100	-40	X	X	-
	Porcelain	100	-40	X	X	-
	Stainless steel	100	-40	X	X	-
	Unsaturated polyester - thermoset	100	-40	X	X	-
	Acrylonitrile butadiene styrene	80	-40	X	X	-
	Polypropylene	80	-	X	-	-
	Polystyrene	80	-40	X	X	-
<b>MIRMYR VI</b>						
	Acrylic paint	150	-40	X	X	-
	Alkyd paint	150	-40	X	X	-
	Aluminum	150	-40	X	X	G, O
	Epoxy paint	150	-40	X	X	-
	Epoxy powder paint	150	-40	X	X	-
	Galvanized steel	150	-40	X	X	-
	Polyester paint	150	-40	X	X	-
	Polyester powder paint	150	-23	X	X	-
	Polyurethane powder paint	150	-40	X	X	-
	Porcelain	150	-40	X	X	-
	Stainless steel	150	-40	X	X	-
	Melamine	100	-40	X	X	-

	Nylon - Polyamide	100	-40	X	X	-
	Phenolic - Phenol Formaldehyde	100	-40	X	X	-
	Polycarbonate	100	-40	X	X	-
	Polyethylene	100	-40	X	X	-
	Polyvinyl chloride	100	-40	X	X	-
	Unsaturated polyester - thermoset	100	-40	X	X	-
	Acrylonitrile butadiene styrene	80	-40	X	X	-
	EPDM rubber	80	-40	X	-	-
	Polybutylene terephthalate	80	-40	X	X	-
	Polypropylene	80	-	X	-	-
	Polystyrene	80	-40	X	X	-
<b>MIRMYR VII</b>						
	Acrylic paint	125	-40	X	X	-
	Alkyd paint	125	-40	X	X	-
	Aluminum	125	-40	X	X	G, O
	Copper	125	-40	X	X	-
	Epoxy paint	125	-40	X	X	-
	Epoxy powder paint	125	-40	X	X	-
	Galvanized steel	125	-40	X	X	-
	Polyester paint	125	-40	X	X	-
	Polyester powder paint	125	-23	X	X	-
	Polyurethane powder paint	125	-23	X	X	-
	Porcelain	125	-40	X	X	-
	Stainless steel	125	-40	X	X	-
	Melamine	100	-40	X	X	-
	Nylon - Polyamide	100	-40	X	X	-
	Phenolic - Phenol Formaldehyde	100	-40	X	X	-
	Polycarbonate	100	-40	X	X	-
	Polyethylene	100	-40	X	X	-
	Polyvinyl chloride	100	-40	X	X	-
	Unsaturated polyester - thermoset	100	-40	X	X	-
	Acrylonitrile butadiene styrene	80	-40	X	X	-
	EPDM rubber	80	-40	X	-	-
	Polybutylene terephthalate	80	-40	X	X	-
	Polypropylene	80	-	X	-	-
	Polystyrene	80	-40	X	X	-
<b>MIRVY IV</b>						
	Acrylic paint	100	-40	X	X	-
	Alkyd paint	100	-40	X	X	-
	Nylon - Polyamide	100	-40	X	X	-
	Stainless steel	100	-40	X	X	-
	Aluminum	80	-40	X	X	-
	Epoxy powder paint	80	-40	X	-	-
	Southern yellow pine	80	-	X	-	-
	Unsaturated polyester - thermoset	80	-	X	-	-
	Galvanized steel	60	-40	X	X	-
	Polyester paint	60	-40	X	X	-
	Acrylonitrile EPDM styrene	40	-40	X	X	-
	Acrylonitrile butadiene styrene	40	-40	X	X	-
	Polyethylene	40	-40	X	X	-
	Polyphenylene oxide/ether	40	-40	X	X	-
	Polypropylene	40	-40	X	X	-
	Polystyrene	40	-40	X	X	-

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

G - Occasional exposure to Gasoline splashing.

O - Occasional exposure to Lubricating Oil.

Marking: Company name and model designation.

[Last Updated](#) on 2016-08-09

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".