

PGDQ2/PGDQ8 MH14014

Marking and Labeling Systems – Component

MIRMYR	Max Temp	Min Temp	Indoor Use	Outdoor Use	Additional Comments
Alkyd paint (AK PT)	302°F/150°C	-40°F/-40°C	X	-	O
Aluminum (AL)	302°F/150°C	-40°F/-40°C	X	-	O
Epoxy paint (EP PT)	302°F/150°C	-	X	-	-
Galvanized steel (GS)	302°F/150°C	-40°F/-40°C	X	-	O
Melamine (ME)	212°F/100°C	-20°F/-29°C	X	-	O
Nylon - polyamide (PA)	212°F/100°C	-20°F/-29°C	X	-	O
Phenolic - Phenol Formaldehyde (PH)	212°F/100°C	-20°F/-29°C	X	-	O
Polycarbonate (PC)	212°F/100°C	-20°F/-29°C	X	-	O
Polyester paint (PER PT)	212°F/100°C	-20°F/-29°C	X	-	O
Polyester powder paint (PER PDR PT)	212°F/100°C	-40°F/-40°C	X	-	-
Porcelain (PRCLN)	212°F/100°C	-20°F/-29°C	X	-	O
Stainless steel (SS)	212°F/100°C	-20°F/-29°C	X	-	O
Acrylic paint (AC PT)	176°F/80°C	-40°F/-40°C	X	-	O
Acrylonitrile butadiene styrene (ABS)	176°F/80°C	-40°F/-40°C	X	-	O
Polypropylene (PP)	176°F/80°C	-	X	-	O
Polystyrene (PS)	176°F/80°C	-20°F/-29°C	X	-	O
Unsaturated polyester - thermoset (UP)	176°F/80°C	-40°F/-40°C	X	-	O
MIRMYR (Type A)					
Metals	212°F/100°C	-	X	-	-
Plastic Group I	212°F/100°C	-	X	-	-
Plastic Group II	176°F/80°C	-	X	-	-
Plastic Group III	176°F/80°C	-	X	-	-
Plastic Group V	176°F/80°C	-	X	-	-
Plastic Group VI	176°F/80°C	-	X	-	-
Plastic Group VII	176°F/80°C	-	X	-	-
Plastic Group VIII	176°F/80°C	-	X	-	-

G - Occasional exposure to Gasoline splashing.
O - Occasional exposure to Lubricating Oil.